

PS-32

Full featured, lightweight and easy to operate

Entry model. Easy operation, fitted with professional features. Very easy starting.




Easy Start: Spring assisted starter combined with optimized engine management



Touch&Stop one lever operating



Fuel pump (Primer)



Metal spike bar

Technical specifications

| | | | |
|--------------------|---------------------|---------------------|--------------------|
| Displacement | 32 cc (1.95 cu. in) | Chain tensioning | Lateral tensioning |
| Power rating | 1.35 kW (1.8 HP) | Automatic oilpump | yes |
| Max engine speed | 12,800 rpm | Catalytic converter | yes |
| Net weight | 4.1 kg (9.02 lbs) | Standard guide bar | 14" |
| Fuel tank capacity | 0.4 l (13.5 oz) | Optional guide bars | 16" |
| Oil tank capacity | 0.28 l (9.5 oz) | Chain pitch | 3/8 " |
| Vibration damping | yes | Chain gauge | .050 " |

- Easy Start: Spring assisted starter combined with optimized engine management significantly reduces resistance
- Touch&Stop one lever control with clearly defined positions for cold starting, operation and stop. Engines shuts off with just a touch.
- Primer pump
- MPI technology (Memory-Power-Ignition) for easy restart
- Metal spike bar as standard
- SafetyMatic chain brake.
- Professional quality centrifugal clutch
- Outside sprocket
- Adjustable metal oil pump
- Catalytic converter to clean the exhaust gases
- Big tank cap, easy reachable. S-form with acme thread for easy operation
- 33 cm markings on the rear handle for cutting wood to length
- 4 steel springs for low vibration
- Lateral chain tensioning
- Two bar studs for reliable bar fastening

DOLMAR Power Products • PO Box 5007 • Alpharetta, GA 30023-5007

www.dolmarpowerproducts.com

www.dolmar.com

